

TimberSaver[®] PT



TimberSaver[®] wood treatment solutions provide protection against attack from termites and fungal decay in dry interior applications.

DECAY AND TERMITE PROTECTION FOR INTERIOR FRAMING

Termite attack on wooden structures in the United States leads to billions of dollars in damages each year. Formosan termite activity in Hawaii and the southern US has been well documented, and has led to a significant increase in the frequency and severity of termite damage caused to homes and commercial structures. Wood frame construction made with TimberSaver PT pressure treated wood is protected against damage from both decay and Formosan termites.

- Non-corrosive to metal fasteners
- Does not adversely affect the strength properties of the treated lumber or plywood
- Meets state of Hawaii requirements for protection against Formosan termites
- Backed by a 20-year limited warranty against Formosan and other termite species, and fungal decay in dry interior applications



VIANCE[®]
T R E A T E D W O O D . C O M

Viance, LLC | 8001 IBM Dr, Charlotte, NC 28262 | 800-421-8661 | Fax 704-527-8232 | treatedwood.com

TimberSaver® PT



TimberSaver PT borate treated wood can be sawn, nailed, drilled, stained and assembled using standard fastener systems typically used in general wood construction practices

TimberSaver PT protected wood is backed with a 20-year limited warranty.

TimberSaver® PT lumber and plywood is pressure-treated with a borate-based wood preservative (Disodium Octoborate Tetrahydrate - DOT) that protects against Formosan and other termite species, and fungal decay in dry interior applications.

- Standardized by the American Wood Protection Association (AWPA) T1, U1, P25 and Use Categories UC1 and UC2 and verified by independent third-party product inspection.
- Available in a wide selection of lumber, timber and plywood species, including Douglas fir.

Applications

- Framing lumber
- Floor joists
- Plywood
- Flooring
- Blocking
- Studs
- Roof rafters
- Interior sheathing
- Moldings
- Beams
- Sill plates
- Trusses
- Furring strips
- Wood trim

PRODUCT	DOT ¹ RETENTION (LBS/CU.FT.)	Boric Oxide (B ₂ O ₃) Equivalents (LBS/CU.FT.)	APPLICATIONS
TimberSaver® PT	0.25	0.17	Applications not subject to attack by Formosan termites
TimberSaver® PT	0.42	0.28	For use in regions where Formosan termites are present, or other severe, weather-protected environments.

¹ Disodium Octoborate Tetrahydrate (DOT)

Nails, Fasteners and Connectors

Corrosion test data shows that borate treated wood has connector corrosion rates similar or equal to untreated wood; however, building codes require the use of corrosion-resistant connectors in contact with all treated wood. Contact connector manufacturers for up-to-date recommendations on specific connectors for use with your treated wood product.

Safe Practices

- Wear gloves when working with wood.
- Wear a dust mask when machining any wood to reduce the inhalation of wood dusts.
- Wear appropriate eye protection to reduce the potential for eye injury from wood particles and flying debris during machining.
- Wash hands thoroughly with mild soap and water after working with treated wood.
- All sawdust and debris should be cleaned up and disposed of after construction in accordance with local waste management regulations.
- Do not burn pressure-treated wood.
- Wash work clothes separately from other household clothing before reuse. Pressure-treated wood should not be used where it may come into direct or indirect contact with drinking water, except for uses involving incidental contact such as fresh water docks and bridges.
- Do not use pressure-treated wood in circumstances where the preservative may become a component of food, animal feed or beehives.
- Do not use pressure-treated wood for mulch.
- Treated wood should be disposed of in landfills or burned in commercial or industrial incinerators or boilers in accordance with federal, state and local regulations.

Standardized 3-part specifications are available at treatedwood.com and ARCAT.com.



TimberSaver® treated wood products are produced by independently owned and operated pressure treating wood facilities.*

See TimberSaver®PT Warranty for details at treatedwood.com

TimberSaver® and Viance are registered trademarks of Viance, LLC.

AWPA is a registered trademark of the American Wood Protection Association.

All logos and trademarks are exclusive property of their respective owners.

© Viance, LLC 2019. All rights reserved. PMG 751 012019